



# AccoFlow™ 200

## technical specifications

### Description

AccoFlow 200 is an aqueous dispersion of cationically-modified bentonite clay. The dispersion contains a relatively high level of clay, in the range of about 20-40% by weight, yet it is amenable to pumping. The product was designed to function as a coagulation/flocculation aid in wastewater systems where cationic coagulants can be effective.

### PERFORMANCE DATA

Wastewater	Treatment/ 100 g of Wastewater			Post-treatment Turbidity (%Transmittance @ 620 nm)	Comments
	AccoFlow (36-39% Clay), g	15% Alum, g	1% Anionic Flocculant, g		
Industrial Wastewater 1	0.0	0.3	0.6		No Clarification
Industrial Wastewater 1	0.25-0.35	0.3	0.6	94-97	
Industrial Wastewater 2	0.3	0.0	0.3	98	
Laundry Wastewater	0.03	0.0	0.3	95	

The information and data contained herein are believed to be accurate and reliable. CETCO OILFIELD SERVICES COMPANY makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information. REV 7/08

### Application Instructions

- 1.The product may be used neat or after dilution (5x-10X) with water, depending on the level of suspended solids in the wastewater, in order to avoid the “overdosing” scenario typically encountered in the use of cationic coagulants. An optimum dosage may be determined using jar testing.
- 2.Dilution (5x-10x) of the product is also recommended when the concentrated product cannot be mixed in easily with the wastewater (for example, as might be the case in certain strongly acidic wastewater systems).

WATER TREATMENT | PIPELINE | WELL TESTING | WASTEWATER | RENTALS | NITROGEN | REELED TUBING



**CETCO**  
**OILFIELD**  
**SERVICES**  
**COMPANY**

800.527.9948

[www.cetcooilfieldservices.com](http://www.cetcooilfieldservices.com)