



# Liqui-Sorb® 200

## technical specifications

### Description

Liqui-Sorb 200 is a proprietary solid, granular super-absorbent polymer that rapidly absorbs and retains aqueous matter. Liqui-Sorb 200 is made from a non-biodegradable polymer that is designed for use on waste that fails the Paint Filter Liquids Test (PFLT).

CHARACTERISTICS		TOXICITY ANALYSIS			PARTICAL SIZE	
			EPA Standard ppm	Typical ppm	U.S. Standard Sieve Size	% Retained
Color	White	Arsenic	5.0	0	30 mesh	13.8
Moisture Content	6-9 %	Barium	100.0	0	50 mesh	56.3
Bulk Density (lbs/ft <sup>3</sup> )	42±2	Cadmium	1.0	0	70 mesh	18.6
		Chromium	5.0	0	100 mesh	9.8
		Lead	5.0	0	200 mesh	1.5
		Mercury	0.2	0	-200 mesh	0
		Selenium	1.0	0		
		Silver	5.0	0		

The information and data contained herein are believed to be accurate and reliable. CETCO OILFIELD SERVICES COMPANY makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information. REV 7/08

### Benefits

- Requires no mixing action to absorb free liquids in the waste.
- Will not increase volume of waste being treated.
- Helps waste pass Toxicity Characteristic Leaching Procedure (EPA Method 1311).
- Will not release liquids after freezing and reheating to 160° F.
- Will not release trapped ionic contaminants if solute evaporation occurs.

WATER TREATMENT | PIPELINE | WELL TESTING

WASTEWATER

RENTALS | NITROGEN | REELED TUBING



**CETCO**  
**OILFIELD**  
**SERVICES**  
**COMPANY**

800.527.9948

[www.cetcooilfieldservices.com](http://www.cetcooilfieldservices.com)