



# Sorbond® UP

## technical specifications

### Description

Sorbond UP is a powdered, clay based stabilization media used for the fixation of free liquids in sludge. Sorbond UP is made from a non-biodegradable mineral that is designed for use on waste that fails the Paint Filter Liquids Test (PFLT).

CHARACTERISTICS		TOXICITY ANALYSIS			PARTIAL SIZE	
			EPA Standard ppm	Typical ppm	U.S. Standard Sieve Size	% Retained
Color	Beige	Arsenic	5.0	0.005	30 mesh	0
Moisture Content	6-9 %	Barium	100.0	0.4	50 mesh	0
Bulk Density (lbs/ft³)	70±2	Cadmium	1.0	0.005	70 mesh	0
pH (5% dispersion):	9.0-11.0	Chromium	5.0	0.005	100 mesh	1.4
Specific Gravity:	2.5±0.5	Lead	5.0	0.05	200 mesh	17.7
		Mercury	0.2	0.02	-200 mesh	80.9
		Selenium	1.0	0.02		
		Silver	5.0	0.005		

The information and data contained herein are believed to be accurate and reliable. CETCO OILFIELD SERVICES COMPANY makes no warranty of any kind and accepts no responsibility for the results obtained through application of this information. REV 7/08

### Benefits

- Absorbs 7.5 times its own weight in water
- Sets up in 24-72 hours
- Helps waste pass Toxicity Characteristic Leaching Procedure (EPA Method 1311)
- Minimal humidity effects

WATER TREATMENT | PIPELINE | WELL TESTING | WASTEWATER | RENTALS | NITROGEN | REELED TUBING



**CETCO**  
**OILFIELD**  
**SERVICES**  
**COMPANY**

800.527.9948

[www.cetcooilfieldservices.com](http://www.cetcooilfieldservices.com)